

A755 GPRS SDI-12

The A755 GPRS SDI provides users with a cost effective means of logging multi-parameter sensors which make use of the SDI-12 protocol.

The A755 can record up to 40 SDI-12 sensor values and is also fitted with a single pulse input for connection to rain gauges or flow meters.

The A755 is housed in a robust aluminium case. Sensor and power connections are made using waterproof Binder connectors. Power comes from an internal NiMH battery which is charged using a compact solar panel. A single use Lithium-Thionyl battery is also available.

Applications

- Weather stations
- Soil moisture monitoring
- Science, research & development, and much more



Technical data

Dimensions	160 x 60 x 80 mm	Operating time (without charging of internal battery)	in standard mode up to 21 days, in power-save mode up to 6 months; depends on slot-time, transmission rate, and sensors
Weight	1,150 g	Frequency range	850 / 900 / 1800 / 1900 MHz
Ingress Protection class	IP-67	Rx Sensitivity	-106 dBm
Temperature range	-30°C to +65°C	Tx Output Power	max. 2 W (depends on frequency)
Case	powder-coated aluminum	Transmission distance	max. 36km as per GSM standard
Screw connections	flange sockets of nickel-plated brass, stainless cover screws	Expansion (optional)	internal Modbus IF via RS 485
Connectors (all connectors IP67 if properly mated or capped)	1x Binder M9 7-pin to SDI-12 1x Binder M9 5-pin to solar cell / power supply 1x TNC Antenna connector	Antenna	omnidirectional quad-band, 2dBi
Power supply	6.2 V NiMH battery 3.1Ah + solar panel / mains adapter	Type approvals	ACMA Australia, R&TTE, FCC Part 15, Industry Canada, etc.
SDI-12 Bus Port	supports up to 40x SDI-12 values	Ordering Information:	
Pulse input	1x pulse counter, max. 30Hz	100.755.010	A755 GPRS SDI
Sampling interval	user specific (from 10sec. to 12h); sensor restrictions apply	200.733.522	Solar Panel, 460mA
Internal memory	2MB for up to 500,000 values	200.800.017 / .018	Cable to SDI-12 sensor, 5m / 10m
		800.000.466	SDI-12 cabling box
		900.000.567	ext. GSM antenna for mast mounting